



PREMIUM SPA STEP THREE STEPS

Hy-Clor's Premium Spa Step - Three Step is easy to assemble and can handle a maximum bearing weight of 150kg.

INSTALLATION INSTRUCTIONS

List of Contents		
NO	QTY	Shape /Name
①	6	
②	1	L
③	1	R
④	1	L
⑤	1	R
⑥	2	
⑦	3	
⑧	4	6x50
⑨	4	M6
⑩	40	ø18
⑪	4	5x16
⑫	4	5x25
⑬	36	6x40
⑭	8	ø9
⑮	1	
⑯	1	ø3.2
⑰	1	5#

Step 1

Attach both left frames ④ & ② and both the right frames ⑤ & ③ using screws ⑧ and washers ⑩

Step 2

Fix step treads ① and spacer ⑦ to the frame using the washer ⑩ & bolts ⑬. Repeat for each of the three steps.

Step 3

Attach brackets ⑥ with fastener ⑪ into the side frame & ⑫ into the top frame. Brackets are placed on the left and right side of the third step.

Step 4

These holes are for installing the handrail on the 3 step or 4 step, either on the right or left side, as preferred. Unused holes can be covered with the provided plugs

SAFETY PRECAUTIONS

Regularly inspect the steps for any signs of damage. Ensure the steps are placed on a flat and stable surface to prevent tipping or shifting; do not use them on a slippery surface. Keep the steps out of reach of small children and ensure they are under competent adult supervision when in use. Use caution when the steps are wet, as they may become slippery. Avoid prolonged exposure to extreme temperatures, as this can weaken the plastic.